

TECHNICAL SPECIFICATIONS PVC 530



PERFORMANCE	STANDARD / TEST	STANDARD PVC	LOW TEMP PVC	ANTI-STATIC PVC	UNIT
SPECIFIC DENSITY	DIN 53 479	1.22	1.20	1.22	g/cm ³
SHORE A HARDNESS	DIN 53 505	75	65	80	-
COLD BEND BRITTLE POINT	DIN 53 372	-35	-45	-35	°C
TEMPERATURE RESISTANCE	-	+50/-20	+35/-40	+0/+50	°C
FLEXIBILITY	BASED ON DIN 51 949	-35	-40	-35	°C
WATER ABSORPTION	DIN 53 742	17	21	17	mg
ELONGATION AT BREAK	DIN 53 455	360	400	240	%
TENSILE STRENGTH	DIN 53 455	17	13	16	n/mm ²
LIGHT TRANSMISSION	ASTM D 1003	>80	>75	>80	%
SOUND PROTECTION	DIN 52 210	>35	>35	>35	dB
FLAMMABILITY	DIN 53 382	Self-Extinguishing	Self-Extinguishing	Self-Extinguishing	-
ANTI-STATIC	-	-	-	YES	-
ANTI-STATIC COMPOUND CONFIRMATION	-	-	-	INEOS EVICOM WE 7851 AS	-

PVC-Strip reserves the right to alter any of the elements quoted in the above specification without prior notice

IF YOU HAVE ANY QUESTIONS, PLEASE CONTACT OUR EXPERIENCED TEAM

SALES@PVC-STRIP.CO.UK

01925 638753

WWW.PVC-STRIP.CO.UK